

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)***(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.  
1334

Total Pages in this Submission

**TO THE ASSISTANT COMMISSIONER FOR PATENTS**Box Patent Application  
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for invention entitled:

**METHOD FOR MOTION-COMPENSATED PREDICTION OF MOVING IMAGES AND DEVICE FOR PERFORMING SAID METHOD**

and invented by:

**Hans-Georg MUSMANN, Thomas WEDI**If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: \_\_\_\_\_

Enclosed are:

**Application Elements**

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 18 pages and including the following:
  - a. ☒ Descriptive Title of the Invention
  - b. ☐ Cross References to Related Applications *(if applicable)*
  - c. ☐ Statement Regarding Federally-sponsored Research/Development *(if applicable)*
  - d. ☐ Reference to Microfiche Appendix *(if applicable)*
  - e. ☒ Background of the Invention
  - f. ☒ Brief Summary of the Invention
  - g. ☒ Brief Description of the Drawings *(if drawings filed)*
  - h. ☒ Detailed Description
  - i. ☒ Claim(s) as Classified Below
  - j. ☒ Abstract of the Disclosure

**UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Large Entity)**

*(Only for new nonprovisional applications under 37 CFR 1.53(b))*

Docket No.  
1334

Total Pages in this Submission

**Application Elements (Continued)**

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☒ Formal                      Number of Sheets 4
- b. ☐ Informal                      Number of Sheets \_\_\_\_\_
4. ☒ Oath or Declaration
- a. ☐ Newly executed *(original or copy)*                      ☒ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney                      ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application,  
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied  
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby  
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

**Accompanying Application Parts**

8. ☐ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☐ Information Disclosure Statement/PTO-1449                      ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class                      ☒ Express Mail *(Specify Label No.):* EF 042303152 US

# UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.  
1334

Total Pages in this Submission

## Accompanying Application Parts (Continued)

15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)

16. ☐ Additional Enclosures (please identify below):

JCE41 U.S. PTO  
09/694211  
10/23/00

## Fee Calculation and Transmittal

### CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	8	- 20 =	0	x \$18.00	\$0.00
Indep. Claims	2	- 3 =	0	x \$80.00	\$0.00
Multiple Dependent Claims (check if applicable) <input checked="" type="checkbox"/>					\$270.00
BASIC FEE					\$710.00
OTHER FEE (specify purpose)					
TOTAL FILING FEE					\$980.00

- ☐ A check in the amount of \_\_\_\_\_ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 19-4675 as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of \$980.00 as filing fee.
  - ☒ Credit any overpayment.
  - ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
  - ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

  
Signature

Dated: OCTOBER 23, 2000

CC:

**BE IT KNOWN** that **WE**, Hans-Georg MUSMANN and Thomas WEDI,  
citizens of Germany, whose post office addresses and residencies are,  
respectively, Heckenrosenweg 24, 38259 Salzgitter 51, Germany; and In der  
Steinriede 12, 30161 Hannover, Germany; have invented certain new and useful  
5 improvements in a

**METHOD FOR MOTION-COMPENSATED PREDICTION OF MOVING  
IMAGES AND DEVICE FOR PERFORMING SAID METHOD**

10 of which the following is a complete specification thereof:

## Background of the Invention

### 1. Field of the Invention

The present invention relates to a method for motion-compensated prediction of moving images or pictures using an interpolation method. It also  
5 relates to a device for performing the said method.

### 2. Prior Art

Standard methods for coding of moving images or pictures (H. 263, MPEG-2, MPEG-4, etc) are based on the principle of the so-called hybridized  
10 coding, as described in ISO/IEC 14496-2, "Final Draft International Standard of MPEG-4", Atlantic City, October 1998, MPEG98/N2502. Fig. 1 is a block diagram of a hybrid video-encoder with motion-compensated prediction. The actual picture signal  $s(t)$  to be coded with the help of the motion-compensated prediction (motion compensation MC) is predicted from the previously  
15 transmitted reference picture  $s'(t-1)$ . The motion-compensated prediction is performed with the help of a so-called block-wise motion vector  $d(t)$ , which is determined with the help of a motion estimation (motion estimation ME). It gives the position of the block used for prediction in the already transmitted reference picture  $s'(t-1)$  for each block of size  $8 \times 8$  and/or  $16 \times 16$  image points of the  
20 actual picture. The result of the motion-compensated prediction is the prediction signal  $\hat{s}(t)$ . The residual prediction error  $e(t) = s(t) - \hat{s}(t)$  and the motion vector  $d(t)$  are coded at the output of the intraframe encoder IE and transmitted. To obtain the reference picture  $s'(t-1)$  the intraframe-encoded prediction error  $e(t)$  is

again decoded (intraframe decoder ID) and added to the prediction signal  $\hat{s}(t)$ .

With the help of a picture memory  $z^{-1}$  the reference picture  $s'(t-1)$  is prepared.

This reference picture  $s'(t-1)$  acts both as an input signal for motion

compensation MC and also for motion estimation ME. The motion estimation ME

5 supplies a motion vector for the respective block of image points with which the motion compensation MC is controlled, i.e. image points of a block are moved with the aid of the motion vector, with the aid of the actual picture  $s(t)$  and the reference picture  $s'(t-1)$ .

In the current standardized coding method the amplitude resolution of the  
10 motion vector amounts to half an image point. For estimation and compensation thus image points must be interpolated in the picture  $s'(t-1)$  between the scanning raster, which corresponds to an increase of the scanning rate of about a factor  $L = 2$ . For example, in the MPEG-4 verification model, as described in the ISO/IEC 14496-2 reference, these image points are produced by bilinear  
15 interpolation filtering of the image points in the scanning raster (see Fig. 2). In the following description the picture interpolated from  $s'(t-1)$  is designated with  $s'u(t-1)$ . The interpolated values "+" are produced by interpolation between the scanned values "O" with the interpolation prescription:

$$A = (A+B)//2, b = (A+B+C+D)//4, c = (A+C)//2.$$
 The symbol "/" represents a  
20 rounded off whole number division. The interpolation and thus the motion-compensated prediction is disturbed by different aliasing in the picture signal  $s(t)$  and the prediction signal  $\hat{s}(t)$  as described in ISO/IEC/SC29/WG11: "Core Experiment on Motion and Aliasing-compensation Prediction (P8)", Stockholm,

July 1997, MPEG97/N1180; in U. Benzler, O. Werner, "Improving Multiresolution Motion Compensating Hybrid Coding by Drift Reduction", Picture Coding Symposium 1996, March 1996, Melbourne; and in WO 99/04574, so that a greater precision for the motion vector using the simple bilinear interpolation permits no additional improvements of coding efficiency. An improved method for making the prediction signal was suggested in ISO/IEC/SC29/WG11: "Core Experiment on Motion and Aliasing-compensation Prediction (P8)", Stockholm, July 1997, MPEG97/N1180 and WO 99/04574 for these reasons. The aliasing signal is reduced in the prediction signal by an N-stage aliasing-reducing "Finite Impulse Response".

### Summary of the Invention

It is an object of the present invention to provide an improved method for motion-prediction of moving images, which does not have the above-described disadvantages.

It is another object of the present invention to provide an apparatus or device for performing this method.

The process for motion-compensated prediction of moving images or pictures using an interpolation method comprises the following steps:

a) considering past image points as well as neighboring image points in the interpolation method;

b) making a motion-compensated picture signal ( $\hat{s}_{tri}(t-1)$ ) using past image point information ( $s_{tri}(t-2)$ ), wherein the image point information is input according to a previously determined motion vector; and

c) inserting the image point information of the motion-compensated picture signal ( $\hat{s}_{tri}(t-1)$ ) in an interpolation raster between the image points of a reference picture.

According to the invention the device for performing this method comprises means for increasing the scanning rate of the reference picture, means for a recursive motion compensation of the reference picture with an image memory for past image point information; a merging module for including motion compensated image point information in an interpolation raster between the image points of the reference picture.

With the features of the device and method according to the invention the prediction signals  $\hat{s}(t)$  related to the picture signal  $s(t)$  are correctly produced including aliasing. Past image points as well as neighboring local image points are used for the interpolation. A reduction of the prediction error and thus an increase in the coding efficiency results when the method according to the invention is used.

An increased amplitude resolution of the motion vector of up to  $1/4$  or  $1/8$  of an image point can be successfully employed with the features of the invention and leads to an additional improvement of the coding efficiency. The scanning rate of the already transmitted reference picture must thus be



increased about a factor of  $L=4$  and  $L=8$  in the horizontal and vertical directions respectively.

The invention is based on the following understanding and knowledge:

Aliasing occurs digitally in the coded picture signal because of a non-

5 ideal low pass in the reception process. The aliasing has the consequence that the picture signal cannot be perfectly reconstructed by a purely local interpolation in the image points between the scanning raster and the motion-compensated prediction cannot predict the picture signal correctly. A prediction error remains, which must be transmitted in coded form. The size of the  
10 prediction error determines the transmission rate and the coding efficiency.

New formulations reduce aliasing in the prediction signal with the help of an FIR filter and improve the coding efficiency as described in WO 99/04574.

However since the picture signal to be coded contains the aliasing, the aliasing in the prediction signal will not be reduced, but conforms with that of the picture  
15 signal  $s(t)$ , in order to reduce the size of the additional prediction error.

The invention is based on the following assumptions: If a non-moving analog picture is scanned at the same position at different times, the  
corresponding scanned values are identical. This is also true for the case in which the scanning frequency is not sufficiently large enough and the scanned  
20 picture signal contains aliasing. If the contents of the analog picture signal move about exactly one image point, the corresponding scanned values are similarly identical and thus have the same aliasing signal. This shows that the aliasing does not effect a prediction of the image contents displaced about an integral

number of image points. Accordingly the method according to the invention for interpolation of intervening values uses past, i.e. temporally previous scanned, values, in order to reconstruct the actual intervening values. For example, if it is known that the image content moves from picture to picture about 1/4 of an image point spacing, one scanning value can be used to reconstruct the image content displaced about 1/4 of an image point spacing in the next picture. Since this scanned value is already on the scanning raster at an earlier time point, it contains the correct image signal with the correct aliasing.

Scanned values from the previous or past pictures are used according to the invention in order to reconstruct the actual intervening values abased on these prerequisites or assumptions. The filter can thus correctly predict the picture signal including the aliasing. It reduces the prediction error and increases the coding efficiency.

### Brief Description of the Drawing

The objects, features and advantages of the invention will now be illustrated in more detail with the aid of the following description of the preferred embodiments, with reference to the accompanying figures in which:

Figure 1 is a block diagram for a device for motion-compensated prediction of moving images or pictures according to the prior art;

Figure 2 is a diagram illustrating interpolation of image points in a picture;

Figure 3 is a block diagram for an interpolation filter for the device for motion-compensated prediction of moving images or pictures according to the invention;

Figure 4 is a diagram illustrating the increase of the scanning rate due to  
5 the method according to the invention for  $L=2$ ;

Figure 5 is a diagram illustrating the operation of the merging module used in the device for performing the method according to the invention;

Figure 6 is a graphical illustration of the experimentally determined rate for synthetic test sequence Syn waves; and

10 Figure 7 is a graphical illustration of the experimentally determined rate for the test sequence "mobile & calendar".

### **Description of the Preferred Embodiments**

15 The block diagram of an interpolation filter shown in Fig. 3 is used in the device for performing the method according to the invention. It is built into the prior art device shown in Fig. 1. The symbols used in Fig. 1, for example  $s'(t-1)$  for the reference picture, are also used in the follow description of Figs. 3 to 7.

20 In a stage or means 1 the scanning rate of the already transmitted reference picture  $s'(t-1)$  is increased by the factor  $L$ . The result of the filtering indicated in Fig. 3 is the interpolated image  $su'(t-1)$ . Since a temporally recursive

filter is used for filtering according to Fig. 3, in the following it is designated as a TRI filter (time-recursive interpolation filter).

The TRI filter comprises three stages. The first stage is the so-called expander 1. The second stage or means includes the recursive structure with the motion compensation 4 and the merging module 3. The third stage or means performs a conventional local interpolation (spatial interpolation). These three stages are described in more detail in the following description.

In a first part, the expander, the scanning rate of the input image - reference image -  $s'(t-1)$  is increased about a factor  $L$ . This occurs because the intervening values of the scanning raster from the reference picture  $s'(t-1)$  are filled with marker values  $m$  (Fig. 4). The marker values  $m$  characterize intervening values which are up to now still not interpolated.

The following equation (1) describes the expander. In this equation  $x$  and  $y$  represent the local image coordinates.

$$S_e(t-1, x, y) = \{s'(t-1, x/L, y/L), \text{ if } x, y = 0, \pm L, \pm 2L, \dots, \\ = m \text{ otherwise}\}. \quad (1)$$

In the second stage or means the past picture  $s_{tri}(t-2)$  is also used in order to replace marked values in the picture with increased scanning rate  $s_e(t-1)$ . This occurs with the help of motion compensation 4 by image points of the past picture  $s_{tri}(t-2)$ , in which the image points are displaced according to their already transmitted motion vector  $L \cdot d(t-1)$ . Thus it should be noted that the

motion vector is multiplied with a factor L, when a picture with a resolution increased by L is used for compensation. In the merging module 3 the values marked in the picture  $s_e(t-1)$  are replaced by the corresponding values from the picture signal  $\hat{s}_{tri}(t-1)$ , which appear at the output of the motion compensation means 4. The following equation (2) describes the merging process, whose result is the picture  $s_{tri}(t-1)$ . In this equation (2) also x and y represent the local picture or image coordinates.

$$s_{tri}(t-1, x, y) = \begin{cases} \hat{s}_{tri}(t-1, x, y), & \text{if } s_e(t-1, x, y) = m; \\ \text{otherwise } s_e(t-1, x, y) \end{cases} \quad (2)$$

Fig. 5 illustrates the operation of the merging module 3. The equation and Fig. 5 show that both pictures  $s_e(t-1)$  and  $\hat{s}_{tri}(t-1)$  are blended or merged to form the picture  $s_{tri}(t-1)$ . At the position where a marker value m is found in the picture  $s_e(t-1)$ , the corresponding image point from the predicated picture  $\hat{s}_{tri}(t-1)$  is used. All remaining values from the picture  $s_e(t-1)$  are taken into the picture  $\hat{s}_{tri}(t-1)$ . Thus the scanning values from the motion-compensated picture  $\hat{s}_{tri}(t-1)$  are used, in order to interpolate the image points (marker values) in the picture  $s_e(t-1)$ .

The third stage or means produces a purely local spatial interpolation according to WO 99/04574 A1, in which the remaining marked values of the

picture  $s_{tri}(t-1)$  exclusively are interpolated. The result is the interpolated picture  $s'u(t-1)$ .

The picture  $s_{tri}(t-1)$  is initialized with the picture  $s_e(t-1)$  at the time point  $t = 1$ , at which no picture  $s_{tri}(t-2)$  exists. The marked values in the picture  $s_{tri}(t-1)$  are  
5 reconstructed by a local interpolation. This corresponds to a conventional purely local interpolation.

Based on the recursive structure, in which image points from the past picture  $s_{tri}(t-2)$  are used, in order to produce the picture  $s_{tri}(t-1)$ , an unlimited dwell time of individual image points in the picture memory 6 ( $s_{tri}$ ) required for  
10 the motion compensation is possible. In order to prevent image point information from remaining for too long a time in the picture memory 6, a counting index is provided for each image point in the memory, which gives the dwell time of the individual image point information. With the help of this index and a threshold value set at the start of the method image point information, which exceeds a  
15 predetermined dwell time in memory, is removed from the picture memory 6. The typical dwell time amounts from three to six of the successive pictures.

The TRI filter, as described in ISO/IEC 14496-2, "Final Draft International Standard of MPEG-4", Atlantic City, October 1998, MPEG98/N2502, was  
integrated in the existing software of the verification model for the experimental  
20 results. Two different modes with different resolutions are supported. In the first case motion vectors with a resolution of a half an image point and a bilinear interpolation are used. In this case the reference method (original code) is

designated with MPEG4-hp and the method with the new TRI filter is designated with TRI-hp (hp - half pel). In the second case motion vectors with a resolution of a fourth image point and an aliasing-reducing Wiener filter are used. In this case the reference method is designated with MPEG4-qp and the new method is  
5 designated with TRI-qp (qp = quarter pel). For the purely local spatial interpolation in the TRI filter the corresponding local interpolation method uses the reference code.

For producing the test results a synthetic and a real test sequence was used in Figs. 6 and 7. The synthetic sequence was produced by scanning two  
10 analogous sine signals, in which the frequency of the first sine signal is below and that of the second sine signal is above half the scanning frequency. Accordingly the second sine signal produces aliasing in the scanned picture signal. Further the analogous picture signal is displaced about exactly a half an image point between successive pictures. This displacement can be estimated  
15 by the code used without error, so that a remaining prediction error can be fed back into an extended interpolation. This synthetic sequence is designated with Syn waves. With the real test sequence it is a matter of the test sequence "mobile & calender".

The results for the synthetic sequence Syn Waves is illustrated in Fig. 6.

20 Although the picture-to-picture displacement of a half an image point can be correctly estimated by all codes, the reference code with the conventional interpolation filter is not in a position to correctly predict the image signal. Accordingly a considerable data rate must be provided for the coding of the

prediction error. The MPEG4-qp coder itself, which operates with an aliasing-reducing Wiener filter, can predicted the picture signal only insufficiently. Accordingly the coder with the TRI filter according to the invention is in a position to predict the picture signal correctly including aliasing, so that a considerably lower data rate is required. The single remaining prediction error is based on the quantization error, which arises in the intra-frame encoder.

In Fig. 7 the results for the real test sequence "Mobile and Calender" are presented. A significant improvement is observed due to the use of the TRI filter according to the invention. An improvement of 0.8 dM has been shown between MPEG4-hp and TRI-hp and an improvement of 0.4 dB has been shown between MPEG4-qp and TRI-qp. The reason for the reduced gain relative to the test sequence Syn waves is because the motion-compensated prediction is disturbed by the displacement estimation error. Also the aliasing signal has no components as large in the total signal as in the synthetic sequence.

The disclosure in German Patent Application 199 51 341.4 of October 25, 1999 is incorporated here by reference. This German Patent Application describes the invention described hereinabove and claimed in the claims appended hereinbelow and provides the basis for a claim of priority for the instant invention under 35 U.S.C. 119.

While the invention has been illustrated and described as embodied in a method and apparatus for motion-compensated prediction of moving images or pictures using an interpolation method, it is not intended to be limited to the



details shown, since various modifications and changes may be made without departing in any way from the spirit of the present invention.

Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it  
5 for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this invention.

What is claimed is new and is set forth in the following appended claims.

**We Claim:**

- 1 1. A process for motion-compensated prediction of moving images or pictures  
2 using an interpolation method, said process comprising the steps of:
  - 3 a) considering past image points as well as neighboring image points in  
4 the interpolation method;
  - 5 b) making a motion-compensated picture signal ( $\hat{s}_{tri}(t-1)$ ) using past  
6 image point information ( $s_{tri}(t-2)$ ), wherein said past image point information is  
7 input according to a previously determined motion vector thereof; and  
8 c) inserting said past image point information of the motion-compensated  
9 picture signal ( $\hat{s}_{tri}(t-1)$ ) in an interpolation raster between image points of a  
10 reference picture ( $s'(t-1)$ ).
- 1 2. The process as defined in claim 1, further comprising producing an  
2 intermediate picture ( $s_e(t-1)$ ) from said reference picture ( $s'(t-1)$ ) by increasing  
3 scanning rate, wherein intervening image points between said image points of  
4 the reference picture ( $s'(t-1)$ ) form said interpolation raster, filling said  
5 intervening image points by marker values ( $m$ ) and replacing said marker values  
6 ( $m$ ) at locations where said past image point information for the motion-  
7 compensated picture signal ( $\hat{s}_{tri}(t-1)$ ) is present.

1 3. The process as defined in claim 2, wherein said marker values (m) that are  
2 not replaced by said past image point information of the motion-compensated  
3 picture signal ( $\hat{s}_{tri}(t-1)$ ) are replaced by locally interpolated image points.

1 4. A device for motion-compensated prediction of moving images or pictures  
2 using an interpolation method, said device comprising means (1) for increasing a  
3 scanning rate of a reference picture, means (4) for a recursive motion  
4 compensation of the reference picture with an image memory (2) for past image  
5 point information; a merging module (3) for including motion-compensated image  
6 point information in an interpolation raster between image points of the reference  
7 picture.

1 5. The device as defined in claim 4, further comprising an interpolation stage (5)  
2 for local interpolation of intervening image points of an interpolation raster not  
3 already occupied in said merging module (3).

1 6. The device as defined in claim 4 or 5, wherein said means (4) for a recursive  
2 motion compensation of the reference picture includes a picture memory (6) and  
3 means for preparing a count index for each newly entered one of said image  
4 points in said picture memory (6), and, when one of said image points has a  
5 value of said count index corresponding to a predetermined dwell time limit, said  
6 one of said image points is removed from said picture memory (6).

- 1 7. The device as defined in claim 4, containing a time-recursive interpolation
- 2 filter.

## ABSTRACT OF THE DISCLOSURE


Past image point information is also considered as well as local neighboring image point information in the interpolation of a predicted picture for motion-compensated prediction of moving pictures with increased resolution.

- 5 Motion-compensated image point information is used in the interpolation raster between the scanned values of the reference picture ( $s'(t-1)$ ) for the predicted picture of increased resolution.

PRIOR ART

*Fig. 1*

The diagram illustrates a prior art motion-compensated video coding system. The input signal  $s(t)$  is split into two paths. One path goes through a summer (indicated by a circle with a plus sign) where a feedback signal  $\hat{s}(t)$  is subtracted (indicated by a minus sign). The resulting error signal  $e(t)$  is then processed by an intraframe encoder (labeled *IE*). The output of the encoder is sent to an intraframe decoder (labeled *ID*). The output of the decoder is added to the feedback signal  $\hat{s}(t)$  at the summer. The output of the summer is then processed by a motion compensation block (labeled *MC*). The output of the motion compensation block is sent to a motion estimation block (labeled *ME*). The output of the motion estimation block is sent to the summer and also to a delay block (labeled  $z^{-1}$ ). The output of the delay block is sent to the motion compensation block and also to a summer where it is added to the output of the motion estimation block to produce the final output signal  $d(t)$ .









Fig. 2

Fig. 4



○ SCANNED VALUE

m MARKER VALUE








Fig. 5



Fig. 7

PSNR [dB]





Fig. 6

PSNR [dB]



# Declaration and Power of Attorney for Patent Application Erklärung für Patentanmeldungen mit Vollmacht

## German Language Declaration

Als nachstehend benannter Erfinder erkläre ich hiermit an Eides  
Statt:

Hans-Georg MUSMANN  
Thomas WEDI

As a below named inventor, I hereby declare that:

Hans-Georg MUSMANN  
Thomas WEDI

dass mein Wohnsitz, meine Postanschrift und meine Staatsangehörigkeit den im nachstehenden nach meinem Namen aufgeführten Angaben entsprechen, dass ich nach bestem Wissen der ursprüngliche, erste und alleinige Erfinder (falls nachstehend nur ein Name angegeben ist) oder ein ursprünglicher, erster und Miterfinder (falls nachstehend mehrere Namen aufgeführt sind) des Gegenstandes bin, für den dieser Antrag gestellt wird und für den ein Patent für die Erfindung mit folgendem Titel beantragt wird:

### VERFAHREN ZUR BEWEGUNGSKOMPENSIERENDEN PRÄDIKTION VON BEWEGTBILDERN SOWIE EINRICHTUNG HIERZU

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

### METHOD FOR MOTION-COMPENSATED PREDICTION OF MOVING IMAGES AND DEVICE FOR PERFORMING SAID METHOD

deren Beschreibung hier beigelegt ist, es sei denn (in diesem Falle Zutreffendes bitte ankreuzen), diese Erfindung

the specification of which is attached hereto unless the following box is checked:

- ☐ wurde angemeldet am \_\_\_\_\_  
unter der US-Anmeldenummer oder unter der  
Internationalen Anmeldenummer im Rahmen des  
Vertrags über die Zusammenarbeit auf dem Gebiet des  
Patentwesens (PCT) \_\_\_\_\_ und am  
\_\_\_\_\_ abgeändert (falls  
zutreffend).

- ☐ was filed on \_\_\_\_\_  
as United States Application Number or PCT  
International Application Number \_\_\_\_\_  
and was amended on \_\_\_\_\_ (if applicable).

Ich bestätige hiermit, dass ich den Inhalt der oben angegebenen Patentanmeldung, einschliesslich der Ansprüche, die eventuell durch einen oben erwähnten Zusatzantrag abgeändert wurde, durchgesehen und verstanden habe.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

Ich erkenne meine Pflicht zur Offenbarung jeglicher Informationen an, die zur Prüfung der Patentfähigkeit in Einklang mit Titel 37, § 1.56 von Belang sind.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Code of Federal Regulations, Regulations, § 1.56.

## German Language Declaration

Ich beanspruche hiermit ausländische Prioritätsvorteile gemäss Title 35, US-Code, § 119 (a)-(d), bzw. § 365(b) aller unten aufgeführten Auslandsanmeldungen für Patente oder Erfinderurkunden, oder § 365(a) aller PCT internationalen Anmeldungen, welche wenigstens ein Land ausser den Vereinigten Staaten von Amerika benennen, und habe nachstehend durch ankreuzen sämtliche Auslandsanmeldungen für Patente bzw. Erfinderurkunden oder PCT internationale Anmeldungen angegeben, deren Anmeldetag dem der Anmeldung, für welche Priorität beansprucht wird, vorangeht.

Prior Foreign Applications  
(Frühere ausländische Anmeldungen)

199 51 341.4 GERMANY

(Number) (Country)  
(Nummer) (Land)

(Number) (Country)  
(Nummer) (Land)

Ich beanspruche hiermit Prioritätsvorteile unter Title 35, US-Code, § 119(e) aller US-Hilfsanmeldungen wie unten aufgezählt.

(Application No.) (Filing Date)  
(Akzenzeichen) (Anmeldetag)

Ich beanspruche hiermit die mir unter Title 35, US-Code, § 120 zustehenden Vorteile aller unten aufgeführten US-Patentanmeldungen bzw. § 365(c) aller PCT internationalen Anmeldungen, welche die Vereinigten Staaten von Amerika benennen, und erkenne, insofern der Gegenstand eines jeden früheren Anspruchs dieser Patentanmeldung nicht in einer US-Patentanmeldung, bzw. PCT internationalen Anmeldung in in einer gemäss dem ersten Absatz von Title 35, US-Code, § 112 vorgeschriebenen Art und Weise offenbart wurde, meine Pflicht zur Offenbarung jeglicher Informationen an, die zur Prüfung der Patentfähigkeit in Einklang mit Title 37, Code of Federal Regulations, § 1.56 von Belang sind und die im Zeitraum zwischen dem Anmeldetag der früheren Patentanmeldung und dem nationalen oder im Rahmen des Vertrags über die Zusammenarbeit auf dem Gebiet des Patentwesens (PCT) gültigen internationalen Anmeldetags bekannt geworden sind.

(Application No.) (Filing Date)  
(Akzenzeichen) (Anmeldetag)

(Application No.) (Filing Date)  
(Akzenzeichen) (Anmeldetag)

Ich erkläre hiermit, dass alle in der vorliegenden Erklärung von mir gemachten Angaben nach bestem Wissen und Gewissen der Wahrheit entsprechen, und ferner dass ich diese eidesstattliche Erklärung in Kenntnis dessen ablege, dass wissentlich und vorsätzlich falsche Angaben oder dergleichen gemäss § 1001, Title 18 des US-Code strafbar sind und mit Geldstrafe und/oder Gefängnis bestraft werden können und dass derartige wissentlich und vorsätzlich falsche Angaben die Rechtswirksamkeit der vorliegenden Patentanmeldung oder eines aufgrund deren erteilten Patentes gefährden können..

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed  
Priorität nicht beansprucht

OCTOBER 25, 1999 ☐  
(Day/Month/Year Filed)  
(Tag/Monat/Jahr der Anmeldung)

(Day/Month/Year Filed)  
(Tag/Monat/Jahr der Anmeldung)

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Status) (patented, pending, abandoned)  
(Status) (patentiert, schwebend, aufgegeben)

(Status) (patented, pending, abandoned)  
(Status) (patentiert, schwebend, aufgegeben)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**German Language Declaration**

VERTRETUNGSVOLMACHT: Als benannter Erfinder beauftrage ich hiermit den (die) nachstehend aufgeführten Patentanwalt (älte) und/oder Vertreter mit der Verfolgung der vorliegenden Patentanmeldung sowie mit der Abwicklung aller damit verbundenen Angelegenheiten vor dem US-Patent- und Markenamt: *(Name(n) und Registrationsnummer(n) auflisten)*

Michael J. Striker, Registration No. 27233

Postanschrift  
STRIKER, STRIKER & STENBY  
103 East Neck Road  
Huntington, NY 11743

Telefonische Auskünfte (Name und Telefonnummer)

Michael J. Striker  
(631) 549 4700

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: *(list name and registration number)*

Michael J. Striker, Registration No. 27233

Send Correspondence to:  
STRIKER, STRIKER & STENBY  
103 East Neck Road  
Huntington, NY 11743

Direct Telephone Calls to:

Michael J. Striker  
(631) 549 4700

Vor- und Zuname des einzigen oder ersten Erfinders Hans-Georg MUSMANN	Full name of sole or first inventor Hans-Georg MUSMANN
Unterschrift des Erfinders Datum	Inventor's signature Date
Wohnsitz Heckenrosenweg 24, 38259 Salzgitter 51, Germany	Residence Heckenrosenweg 24, 38259 Salzgitter 51, Germany
Staatsangehörigkeit GERMAN	Citizenship GERMAN
Postanschrift Heckenrosenweg 24, 38259 Salzgitter 51, Germany	Post Office Address Heckenrosenweg 24, 38259 Salzgitter 51, Germany
Vor- und Zuname des zweitens Erfinders (falls zutreffend) Thomas WEDI	Full name of second joint inventor, if any Thomas WEDI
Unterschrift des Erfinders Datum	Second inventor's signature Date
Wohnsitz In der Steinriede 12, 30161 Hannover, Germany	Residence In der Steinriede 12, 30161 Hannover, Germany
Staatsangehörigkeit GERMAN	Citizenship GERMAN
Postanschrift In der Steinriede 12, 30161 Hannover, Germany	Post Office Address In der Steinriede 12, 30161 Hannover, Germany